




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : H04M 7/00, H04J 3/12	A1	(11) International Publication Number: WO 00/60839 (43) International Publication Date: 12 October 2000 (12.10.00)
<p>(21) International Application Number: PCT/US00/03880</p> <p>(22) International Filing Date: 14 February 2000 (14.02.00)</p> <p>(30) Priority Data: 60/127,889 5 April 1999 (05.04.99) US</p> <p>(71) Applicant (for all designated States except US): TEKELEC [US/US]; 26580 West Agoura Road, Calabasas, CA 91302 (US).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): DUNN, William, Latta, Jr. [US/US]; 103 Oberon Court, Cary, NC 27513 (US). COX, David, Paul [US/US]; 123 Keystone Drive, Cary, NC 27513 (US). RAVISHANKAR, Venkataramaiah [US/US]; 102 Millers Creek Drive, Apex, NC 27502 (US). COLLARD, Colleen, McGinnis [US/US]; 4604 Salem Ridge Road, Holly Springs, NC 27540 (US).</p> <p>(74) Agent: JENKINS, Richard, E.; Jenkins & Wilson, P.A., Suite 1400, University Tower, 3100 Tower Boulevard, Durham, NC 27707 (US).</p>	<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>	

(54) Title: METHODS AND SYSTEMS FOR ROUTING SIGNALING MESSAGES ASSOCIATED WITH PORTED SUBSCRIBERS IN A COMMUNICATIONS NETWORK



(57) Abstract

A routing node (516) for translating and re-directing Signaling System 7 (SS7) messages associated with ported subscribers in a communications network. Re-direction or re-routing of signaling message packets is accomplished without the need for explicit local number portability (LNP) type triggers or queries, and such as the routing node of the present invention is considered to implement a triggerless LNP (TLNP) routing solution. Upon entering the routing node, SS7 ISDN User Part (ISUP) type signaling messages (N1) that require LNP translation service are encapsulated in an SS7 Signaling Connection Control Part (SCCP) message packet and internally routed within the switch to an LNP translation subsystem (518). The LNP translation subsystem (518) can be integrated within the routing node (516) or a portion of the LNP translation subsystem (518) can be located on an external database server platform. LNP translation involves the lookup of a called party (122) address in an LNP database, and the return of a Location Routing Number (LRN). The returned LRN, which is representative of the End Office (EO, 110 & 113) currently servicing the called party (113), is inserted into the original ISUP message (N1) and the resulting modified message (N2) is then routed from the switch.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Description

METHODS AND SYSTEMS FOR ROUTING SIGNALING MESSAGES
ASSOCIATED WITH PORTED SUBSCRIBERS IN A COMMUNICATIONS
5 NETWORK

Priority Application Information

This application claims the benefit of United States Provisional Patent
Application Number 60/127,889, filed April 5, 1999, the disclosure of which is
10 incorporated herein by reference in its entirety.

Technical Field

The present invention relates to the routing of signaling messages in
a communications network, such as the public switched telephone network
15 (PSTN), or a voice over internet protocol (VOIP) network. More particularly,
the present invention relates to methods and systems for routing signaling
messages associated with ported subscribers in a communications network.

Background Art

20 Local number portability (LNP) gives telephone service subscribers
the ability to change local service providers without changing their directory
numbers. More specifically, the generic term LNP is actually representative
of three basic number porting scenarios: service provider portability, which

allows subscribers to change local service providers without changing their phone number; service portability, which allows subscribers to change from one type of service to another (e.g., analog to integrated services digital network (ISDN) without changing their phone numbers; and geographic
5 portability, which allows subscribers to move from one physical location to another without changing their phone numbers.

In the current, non-LNP environment, a telephone number performs two basic functions: it identifies the customer, and it provides the network with information necessary to route a call to that customer. Local number
10 portability solutions separate these two functions, thereby providing the means for customers to keep the same directory number when changing local service providers. By separating these two functions, LNP gives customers the flexibility to respond to pricing and service changes offered by rival carriers. Accordingly, it is anticipated that LNP will promote local-
15 exchange competition, which in turn will benefit all customers, as has already been the case with the long-distance market. As LNP solutions are implemented, competition in the local-exchange market is expected to drive down the cost of service, encourage technological innovation, stimulate demand for telecommunications services, and boost economic growth.

20 A number of interim number-portability methods, such as remote call forwarding and direct inward dialing exist today. However, these methods have several disadvantages: longer call set-up times, increased potential for call blocking, continued reliance on the incumbent local exchange carrier's (LEC's) network, loss of feature functionality, as well as substantial on-going
25 costs to the new local service provider. Among the more long-term LNP

solution approaches currently being offered, triggered LNP technology is the most relevant to a discussion of the present invention.

Triggered LNP Solutions

Triggered LNP solutions, as indicated by the name, require that both
5 the "new" and "old" local service providers implement a trigger function in their respective end offices. The "old" service provider switch (often referred to as the donor switch) administers an LNP trigger on the ported subscriber's directory number. When activated, this trigger causes the end office switch to formulate an LNP query that is subsequently launched into the SS7
10 network. This LNP query is ultimately delivered to an LNP database that contains information related to service provider associated with the dialed number. More particularly, the LNP database performs a lookup based on a portion of the called party dialed digits. A location routing number (LRN) is returned by the LNP database which identifies the end office of the service
15 provider currently serving the called party. The LRN value is then sent back to the end office that originated the LNP query. Upon receipt of the LRN containing message, the originating end office proceeds with call setup and teardown operations using the LRN as a destination address for all subsequent messages associated with the call.

20 Shown in Figure 1 is an example of a telecommunications network, generally indicated by the numeral 100, that employs a triggered LNP solution similar to that described above. Telecommunications network 100 includes an originating end office (EO) 110, a recipient terminating EO 112, a donor terminating EO 113, a tandem switching office 114, a signal transfer
25 point (STP) 116, a service control point (SCP) based LNP database 118, a

calling party 120, and a called party 122. In this example, it is assumed that called party 122 has had local phone service ported from a service provider that owns EO 113 to a service provider that owns EO 112. Consequently, it is implied that the service responsibility for called party 122 was transferred
5 from the donor EO 113 to the recipient EO 112 at some point in the past. As such, EO 112 is now assumed to service called party 122.

As such, Figure 1 illustrates a simplified signaling message flow sequence associated with the setup of a call from calling party 120 to called party 122. When calling party 120 goes off-hook and dials the telephone
10 number associated with called party 122, originating EO 110 analyzes the dialed digits and recognizes that the dialed number falls within an exchange that contains ported subscribers. Consequently, the originating EO 110 formulates an LNP query message M1 and sends this query message to the STP 116. Those skilled in the art of SS7 telecommunication networks will
15 appreciate that such LNP queries and responses are typically in the form of Transaction Capabilities Application Part (TCAP) protocol signaling messages. As the TCAP protocol is well known and widely employed in the communication networks presently contemplated, a detailed discussion of the TCAP signaling protocol is not included herein.

20 Returning now to the message flow shown in Figure 1, LNP query message M1 is received by the STP 116 and subsequently routed to the SCP-LNP database node 118 as LNP query message M2. The LNP query message M2 is processed by SCP-LNP database node 118, and an LNP response message M3 is formulated and sent back to STP 116. It should be
25 appreciated that LNP response message M3 contains a Location Routing

Number (LRN) associated with the recipient EO 112, which is the EO currently servicing Called Party 122. Tandem office 114 is particularly significant from a call setup standpoint, in that a voice trunk connection through tandem 114 will ultimately be required in order to establish a voice circuit with the terminating EO 112 that is currently serving the called party 122. LNP response message M3 is received by the STP 116 and subsequently routed to the originating EO 110, as LNP response message M4. The originating EO 110 processes the LNP response message M4, and uses the LRN information contained therein to formulate and send a call setup message M5. Once again, those skilled in the art of SS7 telecommunication networks will appreciate that such call setup messages are typically of ISDN user part (ISUP) format, and as the ISUP signaling protocol is well known and widely employed in the telecommunications industry, a detailed explanation of this protocol is not provided herein.

15 *Signaling System #7*, by Travis Russell, copyright 1998, McGraw-Hill Publishing, the disclosure of which is incorporated herein by reference in its entirety, provides a detailed explanation of TCAP and ISUP signaling protocols.

Returning to Figure 1, STP 116 receives message M5 and subsequently message transfer part (MTP) routes the message to tandem office 114 as message M6. Tandem office 114 examines and processes the message and formulates a message M7. Message M7 is sent to STP 116, which in turn MTP routes the message to terminating EO 112 as message M8. Those skilled in the art of telecommunications network operations will appreciate that additional call setup and teardown messages, not shown in

Figure 1, may be necessary to administer a complete a telephone call between the calling party 120 and the called party 122. The signaling message flow shown in Figure 1 is intended only to generally illustrate a conventional LNP translation process. As these additional signaling
5 messages are not particularly relevant to the design and operation of the present invention, a detailed discussion of call setup and teardown procedures in an SS7 telecommunications network is not provided herein.

While the approach described above is functionally capable of providing network operators with local number portability translation service,
10 this approach necessarily requires that an originating end office switch have the ability to trigger an LNP query and to interpret the subsequent LNP response. In practice, this means that an originating end office switch must be capable of generating and launching an LNP query message into the signaling network. As such, this also implies that an originating end office
15 switch has the ability to receive and process LNP response messages that are generated by service nodes within the signaling network.

Therefore, what is needed is a novel system and method of routing signaling messages to ported subscribers in a communications network that is transparent to the originating end office and, as such, does not require the
20 originating end office signaling facility to directly generate and respond to number portability related signaling messages.

Disclosure of the Invention

According to one aspect, the present invention includes a
25 communications network element that is capable of performing triggerless

routing of signaling messages associated with calls to ported subscribers. The triggerless routing node includes a communication module capable of transmitting and receiving data packets over a network. A stop action function processes incoming data packets and subsequently directs certain

5 packets to a number portability database manager. The number portability database manager facilitates searching of a number portability database based on called party information contained within the data packets. Routing information returned by the number portability database is incorporated into the data packets, and the modified data packets are then

10 transmitted into the communications network. Because the routing node examines and directly modifies call setup type signaling messages, no explicit translation service trigger messages are required.

Accordingly, it is an object of the present invention to provide a triggerless number portability routing node capable of modifying the content

15 of call setup type signaling messages associated with calls to ported subscribers, so as to include a Location Routing Number associated with the ported subscriber.

Some of the objects of the invention having been stated hereinabove, other objects will be evident as the description proceeds, when taken in

20 connection with the accompanying drawings as best described hereinbelow.

Brief Description of the Drawings

Figure 1 is a network diagram illustrating a conventional LNP solution and associated signaling message flows.

Figure 2 is a schematic diagram of a system architecture according to a preferred embodiment of a triggerless number portability routing node of the present invention.

Figure 3 is a schematic diagram of a conventional signal transfer point switching node with integral number portability database functionality for use in a triggered number portability network architecture.

Figure 4 is a table which illustrates a sample number portability database structure and data used in a preferred embodiment of a triggerless number portability routing node of the present invention.

Figure 5 is a flow chart illustrating SCCP encapsulation related processing of a signaling message according to a preferred embodiment of a triggerless number portability routing node of the present invention.

Figure 6 is a flow chart illustrating SCCP de-capsulation and number portability translation related processing of a signaling message according to a preferred embodiment of a triggerless number portability routing node of the present invention.

Figure 7 is a diagram illustrating an SCCP encapsulated ISUP signaling message.

Figure 8 is a schematic diagram of a system architecture according to another embodiment of a triggerless number portability routing node of the present invention.

Figure 9 is a diagram illustrating a network implementation of a triggerless number portability routing node of the present invention and signaling message flows associated therewith.

Figure 10 is a table which illustrates partial content of a signaling message received and processed by a triggerless number portability routing node of the present invention.

5 Detailed Description of the Invention

According to one embodiment of the present invention, a triggerless number portability routing node is provided. The triggerless number portability routing node is described and illustrated herein as a collection of processes and subsystems that execute on cards to perform triggerless number portability processing. It is understood that these cards each may include one or more general purpose microprocessors and memory devices. Accordingly, the processes, databases, applications, and subsystems described herein may be implemented by computer-executable instructions embodied in a computer-readable medium. Alternatively, the processes, databases, applications, and subsystems described herein may be implemented in hardware as application-specific integrated circuits (ASICs). Any combination of hardware, software, or hardware and software for performing triggerless number portability processing as described herein is intended to be within the scope of the invention.

A preferred system for implementing triggerless number portability functions will be explained in the context of a number portability routing node. Many of the processes, databases, applications, and subsystems that execute within the number portability routing node are referred to herein as local number portability (LNP) processes, databases, applications, and subsystems. It is understood that the functionality implemented by these

LNP entities applies to number portability in general, including, local number, mobile number portability, and any other porting of subscriber numbers. Accordingly, the present invention is not intended to be limited to providing only triggerless local number portability.

5 Shown in Figure 2 is a schematic diagram of a triggerless number portability routing node **300** of the present invention. In the preferred embodiment shown, triggerless number portability routing node **300** employs an internal architecture similar to that of high performance STP and signaling gateway (SG) products which are marketed by the assignee of the present
10 application as the Eagle[®] STP and IP7 Secure Gateway[™], respectively. A block diagram that generally illustrates the base internal architecture of the Eagle[®] STP product is shown in Figure 3. A detailed description of the Eagle[®] STP may be found in the *Eagle[®] Feature Guide* PN/910-1225-01, Rev. B, January 1998, published by Tekelec, Inc. the disclosure of which is
15 hereby incorporated herein by reference in its entirety. Similarly, a detailed description of the IP7 Secure Gateway[™] may be found in Tekelec, Inc. publication PN/909-0767-01, Rev B, August 1999, titled *Feature Notice IP7 Secure Gateway[™] Release 1.0*, the disclosure of which is hereby incorporated herein by reference in its entirety.

20 As described in the above-referenced *Eagle[®] Feature Guide*, an Eagle[®] STP **250** includes the following subsystems: a Maintenance and Administration Subsystem (MAS) **252**, a communication subsystem **254** and an application subsystem **256**. The MAS **252** provides maintenance communications, initial program load, peripheral services, alarm processing
25 and system disks. The communication subsystem **254** includes an

Interprocessor Message Transport (IMT) bus that is the main communication bus among all subsystems in the Eagle® STP 250. This high-speed communications system functions as two 125 Mbps counter-rotating serial buses.

5 The application subsystem 256 includes application cards that are capable of communicating with the other cards through the IMT buses. Numerous types of application cards can be incorporated into STP 250, including: a Link Interface Module (LIM) 258 that provides SS7 links and X.25 links, a Application Communication Module (ACM) 260 that provides a
10 TCP/IP interface over Ethernet, and an Application Service Module (ASM) 262 that provides global title translation, gateway screening and other services. A Translation Service Module (TSM) 264 may also be provided to support triggered local number portability service. Once again, a detailed description of the Eagle® STP is provided in the above cited *Eagle® Feature*
15 *Guide* and need not be described in detail herein. It should also be appreciated that, in addition to conventional SS7 LIM cards, a Database Communication Module (DCM) can be employed in a similar manner to provide for the transport of Internet Protocol (IP) encapsulated SS7 messages over an IP network, as described in the above referenced *Feature*
20 *Notice IP⁷ Secure Gateway™ Release 1.0* publication. With particular regard to the TSM triggered LNP services module mentioned above, a detailed description of the Tekelec, Inc. triggered LNP solution may be found in the *Feature Guide LNP LSMS* PN/910-1598-01, Rev. A, January 1998, published by Tekelec, Inc., the disclosure of which is hereby incorporated
25 herein by reference in its entirety.

Integrated Number Portability Database Embodiment

Referring again to Figure 2, it will be appreciated that triggerless number portability routing node 300 includes a high speed Interprocessor Message Transport (IMT) communications bus 310. Communicatively
5 coupled to IMT bus 310 are a number of distributed processing modules or cards including: a pair of Maintenance and Administration Subsystem Processors (MASPs) 312; a pair of SS7 capable Link Interface Modules (LIMs) 320 and 360; and an LNP Service Module (LSM) 340. These modules are physically connected to the IMT bus 310 such that signaling
10 and other type messages may be routed internally between all active cards or modules. For simplicity of illustration, only a single pair of LIMs 320 and 360 and a single LSM 322 are included in Figure 2. However, it should be appreciated that the distributed, multi-processor architecture of the triggerless number portability routing node 300 facilitates the deployment of
15 multiple LIM, LSM, and other cards, all of which could be simultaneously connected to the IMT bus 310.

MASP pair 312 implement the maintenance and administration subsystem functions described above. As the MASP pair 312 are not particularly relevant to a discussion of the flexible routing attributes of the
20 present invention, a detailed discussion of their function is not provided herein. For a comprehensive discussion of additional MASP operations and functionality, the above-referenced Tekelec, Inc. publications can be consulted.

Focusing now on LIM card functionality, it will be appreciated that LIM
25 320 is comprised of a number of sub-component processes including, but

not limited to an SS7 MTP level 1 process 322, an SS7 MTP level 2 process 324, an I/O buffer or queue 325, a gateway screening (GWS) process 326, a triggerless LNP (TLNP) stop action process 328, an SS7 MTP level 3 layer HMDC process 330, and an HMDT process 332. MTP level 1 and 2 processes 322 and 324, respectively, provide the facilities necessary to send and receive digital data over a particular physical media / physical interface, as well as to provide error detection / correction and sequenced delivery of all SS7 message packets. I/O queue 325 provides for temporary buffering of incoming and outgoing signaling message packets. GWS process 326 is responsible for examining the incoming signaling message and determining which, if any, of the provisioned stop actions are applicable. TLNP stop action process 328 is responsible for encapsulating an incoming SS7 ISUP Initial Address Message (IAM) signaling message packet within an SS7 Signaling Connection Control Part (SCCP) formatted packet. MTP level 3 HMDC process 330 receives signaling messages from the lower processing layers and performs a discrimination function, effectively determining whether an incoming SS7 message packet requires internal processing or is simply to be through switched. The HMDT process 332 handles the internal routing of SS7 message packets that require additional processing prior to final routing. Once again, it should be appreciated that a LIM card may contain more functional processes than those described above. The above discussion is limited to LIM functionality associated with the basic processing of in-bound signaling messages.

As such, it will be appreciated that the three functional processes associated with LIM 360 shown in Figure 2 are simply those processes that

are relevant to a discussion of out-bound LIM operation in the examples of triggerless number portability routing node operation disclosed herein. The processes explicitly shown on the out-bound LIM 360 include an I/O queue 362 and MTP level 1 and 2 processes 366 and 364, respectively. I/O queue 5 362 facilitates temporary buffering of incoming and outgoing signaling message packets. MTP level 2 process 364 and an MTP level 1 process 366, respectively, provide the facilities necessary to send and receive digital data over a particular physical media / physical interface, as well as to provide error detection / correction and sequenced delivery of all SS7 10 message packets.

In general, an LSM card includes the database and database control processes necessary to achieve the triggerless number portability routing functionality of the present invention. The LSM 340 shown in Figure 2 is comprised, in part, of an SCCP subsystem controller known as a Signaling 15 Connection Routing Controller (SCRC) process 342, a Local Number Portability Manager (LNPM) process 344, a Triggerless Local Number Portability (TLNP) application 346, and an LNP database process 348. The SCRC process 342 is responsible for discrimination of signaling messages at the SCCP level, and for distributing the signaling messages to a higher 20 processing level when appropriate. In the configuration shown in Figure 2, the next highest processing level is represented by the LNPM process 344. LNPM process 344 is responsible for determining which specific local number portability application is required for successful processing of a particular incoming signaling message packet. As will be appreciated from

Figure 2, a number of local number portability applications may be simultaneously provisioned on a single LSM card.

While any number or variety of LNP translation applications may be provisioned on a single LSM card, triggerless local number portability (TLNP) application **346** is the most relevant to a general discussion of the present invention. TLNP application **346** essentially contains the logic necessary to de-capsulate the original ISUP IAM message, extract the appropriate information from the de-capsulated message, and perform an associated LNP database lookup. Furthermore, TLNP application **346** is responsible for modifying the signaling message based on the results of the LNP database lookup. In the embodiment shown in Figure 2, an LNP database **348** is co-resident on the LSM card **340**. More particularly, in this embodiment of the present invention, the LNP database **348** is stored in one or more blocks of high speed random access memory (RAM) that is located on the LSM card. As indicated in Figure 4, LNP database **348** is comprised of a number of entries or records, with each record containing at least two fields; a CdPA Address (CdPA:ADD) field, and a Location Routing Number (LRN) field. Once again, it will be appreciated from the discussion above that an LRN identifies the end office of the service provider currently serving the called party.

Referring again to Figure 2, LSM **340** also contains an HMRT process **350** that is responsible for the routing of SS7 message packets once TLNP translation has been completed. That is, the HMRT process **350** determines to which LIM card an SS7 message packet should be routed for subsequent outbound transmission into the communication network.

It will be appreciated from Figure 2 that LSM 340 is in communication with and serviced by a Local Service Management System (LSMS) 370. In general, an LSMS system is also in communication with a Number Portability Administration Center (NPAC). As such, an LSMS acts as the interface
5 between carrier networks and the NPAC. In a typical implementation, an LSMS receives and stores ported subscriber information from the NPAC and then, in turn, is responsible for downloading this ported subscriber information to all the LNP databases which it services. As the interaction between an NPAC and an LSMS is not particularly relevant to the present
10 invention, a detailed discussion of such NPAC-LSMS system functionality will not be presented herein. It should suffice to state that the LSMS 370 maintains the LNP database 348 with the most current ported subscriber information available at any given time.

15 **Integrated Number Portability Database Translation Process**

Continuing with Figure 2, the path of a typical SS7 ISUP IAM signaling message requiring TLNP translation service is traced from reception at the triggerless number portability routing node by the inbound LIM 320, through the translation process, and on to the outbound LIM 360.
20 A detailed flow chart of triggerless number portability related processing steps is presented in Figures 5 and 6, and may be used in conjunction with the schematic diagram shown in Figure 2 to better understand the triggerless LNP lookup methodology.

Beginning with step ST1, an incoming ISUP IAM message is received
25 at the inbound LIM module 320. In steps ST2 and ST3, the incoming ISUP

IAM message is received and processed by the MTP Level 1 and 2 processes 322 and 324, respectively. As stated above, MTP level 1 and 2 processing includes correction, sequencing, and communicating with network error communications hardware. With MTP Level 1 and 2 processing complete, the signaling message packet is temporarily buffered in the I/O queue 325 before being passed up the stack to the MTP Level 3 Gateway Screening (GWS) process 326. As indicated in step ST4, GWS process 326 examines the incoming ISUP IAM message and determines not only whether the message is to be allowed into the switch for further processing, but also which, if any, of the provisioned stop actions are applicable to the incoming message. In this example, GWS process 326 examines the incoming ISUP IAM message and determines that the message is permitted to enter the switch. Furthermore, upon examination of the Originating Point Code (OPC), Destination Point Code (DPC) and Service Indicator Octet (SIO) fields contained in the MTP routing layer, it is determined that the message requires additional processing by the TLNP stop action 328 (ST5).

In step ST6 TLNP stop action process 328 receives the ISUP IAM message from GWS process 326 and determines that the incoming message is an ISUP type MSU. The TLNP stop action process 328 next checks the DPC of the incoming MSU. More specifically, the TLNP stop action verifies that the DPC of the incoming MSU is a valid PC, as indicated in step ST7. In steps ST8 and ST9, TLNP stop action 328 examines the incoming MSU to determine whether LNP service is required. If the incoming MSU is identified as being an ISUP IAM type message (ST8) and

the FCI Ported Number Translation Indicator is equal to zero (**ST9**), TLNP stop action **328** encapsulates the ISUP IAM message within an SCCP formatted MSU, as indicated in step **ST10**. Such SCCP encapsulation is effectively achieved by adding essential SCCP message leading and trailing
5 bit sequences to the base bit sequence that comprises the ISUP IAM MSU, as generally illustrated in Figure 7. Thus, an SCCP type encapsulating MSU is created which envelops or contains an ISUP type MSU. Subsequent to this encapsulation, the incoming message no longer appears or is treated as an ISUP IAM message within the TLNP routing node **300**, but is instead
10 processed internally as an SCCP type SS7 message.

It should be appreciated that during the encapsulation process, the SCCP MSU destination point code (DPC) field value is set to the point code (PC) of the TLNP routing node, the SCCP MSU Called Party Routing Indicator (CdPA RI) field is set to subsystem number (SSN), and the SCCP
15 MSU Called Party Subsystem Number (CdPA SSN) field is set to the LNP SSN of the TLNP routing node. It should also be appreciated that failure of the incoming ISUP MSU to meet the criteria specified in steps **ST5** through **ST9** causes the original, non-encapsulated MSU to be routed directly to HMDC process **330** where normal ISUP MSU type routing is resumed.

20 However, in the case where an incoming ISUP MSU satisfies the **ST5** through **ST9** criteria, SCCP encapsulation of the ISUP MSU occurs and the resulting encapsulated MSU is directed to HMDC process **330**, where SCCP type processing is performed. In the example shown in Figure 2, HMDC process **330** examines the message packet and determines that the DPC of
25 the packet is the PC of the TLNP routing node. Consequently, further

processing of the SCCP MSU within the TLNP routing node is assumed to be necessary, and the packet is passed to the HMDT process 332. The HMDT process 332 examines the Service Indicator (SI) field of the encapsulated MSU, which indicates that the encapsulated packet is of an SCCP type. As such, HMDT process 332 places the encapsulated SCCP MSU on high speed IMT bus 310 for transport to LSM 340 and subsequent LNP translation.

In step ST12, the encapsulated SCCP MSU is received and examined by SCRC process 342 that is resident on LSM 340. Given that the CdPA RI field of the SCCP MSU is set to SSN and the CdPA SSN field of the SCCP MSU is set to the LNP subsystem of the TLNP node 300, SCRC process 342 forwards the encapsulated MSU to the LNPM process 344, as indicated by step ST13. In step ST14, LNPM process 344 verifies that the SCCP MSU contains an encapsulated ISUP MSU. Upon successful verification, the SCCP MSU is sent to TLNP application 346 for further processing. TLNP application processing begins with verification of the pointers and field lengths associated with the ISUP message (ST15). With a positive verification at step ST15, TLNP application 346 next extracts the original ISUP MSU by removing and discarding the SCCP wrapper (ST16). The TLNP application 346 next performs a number of operations intended to validate one or more of the Called Party (CdPA) parameters contained in the original ISUP MSU (ST17). Such validation operations may include, but are not limited to: verification that the Called Party Number exists; verification that the Called Party Number contains 10 digits; verification that the Nature Of Address is national; and verification that the Numbering Plan is ISDN.

With the above described validation process successfully completed, the TLNP application 346 extracts the Called Party Number from the ISUP IAM MSU and uses this value to perform a lookup operation in LNP database 348 (ST18). As indicated in step ST19, the Translated Call
5 Number Indicator (TCNI) field contained within the ISUP IAM message is set to a value of one. It should be appreciated that the TCNI field is set to a value of one regardless of whether a match is found during the LNP lookup operation. In the event that an entry exists in the LNP database 348 which corresponds to the Called Party Number value in the ISUP IAM message,
10 the Called Party Number is considered to be associated with a ported subscriber (ST20) and LNP database process 348 returns a Location Routing Number (LRN). Prior to incorporation of the LRN value in the ISUP MSU, the original CdPA Number value used in the LNP database lookup is stored in a Generic Address Parameter (GAP) field, which is also contained
15 within the ISUP MSU (ST21). Subsequently, the CdPA Number field of the ISUP MSU is overwritten with the LRN value returned by the LNP database process 348, as indicated in step ST22.

As further indicated in step ST23, a value known as a Jurisdiction Information Parameter (JIP) may be appended to the TLNP processed ISUP
20 MSU under certain conditions. The JIP is used in LNP type applications to support billing systems. Such telecommunication billing systems might otherwise have difficulty determining the correct billing for an originating number that has been ported. As such, a valid JIP contains a value that represents the origin of the call. The value may be some of the digits from
25 the calling party address or, alternatively, an identifier associated with the

end office that originated the call. A service provider may negotiate to use a single JIP to represent all messages from its own network, or a service provider may chose to provide a list of the exchanges in its network that can be used as the JIP value. In the TLNP routing node **300** shown in Figure 2,
5 a JIP parameter may be added to the ISUP IAM message by TLNP process **346** if a JIP does not already exist in the original MSU and a JIP value is provisioned in LNP database **348**. A JIP parameter may also be added by TLNP process **346** if the original IAM MSU contains a valid Calling Party (CgPA) Number but does not already contain a JIP value.

10 With TLNP processing complete, the modified ISUP MSU is passed to HMRT process **350**. HMRT process **350** determines to which LIM card an SS7 message packet should be routed for subsequent outbound transmission. In this case, the HMRT process **350** determines that the desired outbound signaling link associated with the routing of the modified
15 ISUP MSU is located on LIM **360**. Consequently, the modified signaling message packet is internally routed across the IMT bus **310** to LIM **360**, where it is generally received by the I/O queue process **362**. Eventually, the modified message packet is passed from the I/O queue **362** on to the MTP Level 2 and Level 1 processes **364** and **366**, respectively. Once again, MTP
20 level 1 and 2 layer processes **366** and **364**, respectively, provide the facilities necessary to send and receive digital data over a particular physical media / physical interface, as well as to provide error detection / correction and sequenced delivery of all SS7 message packets transmitted into the SS7 network.

External LNP Database Server Embodiment

Another embodiment of the present invention is shown in Figure 8. Included in this embodiment is a triggerless LNP routing node **400**, which is further comprised of a pair of LIM modules **320** and **360**, a pair of MASP processors **312**, an IMT communication bus **310**. Also included in the embodiment shown in Figure 8 is an LSMS **370**. The above mentioned components are essentially identical in function to the corresponding components previously described for the embodiment shown in Figure 2. Consequently, a detailed description of these system components is not repeated in the discussion that follows.

It will be appreciated that the LSM card **340** of the previously described embodiment is replaced by an LSME card **410** and an external LNP database server **450**. From an operational perspective, LSME module **410** and external LNP database server **450** provide essentially the same functionality as the integrated LSM module **340**, previously described above and shown in Figure 2.

LSME module **410**, shown in Figure 8 is comprised, in part, of an SCCP subsystem controller known as a Signaling Connection Routing Controller (SCRC) process **412**. The SCRC process **412** is responsible for discrimination of signaling messages at the SCCP level, and for distributing the signaling messages to a higher processing level when appropriate. In the configuration shown in Figure 8, the next highest processing level is represented by a Local Number Portability Manager (LNPM) process **414**. LNPM process **414** is responsible for determining which specific Local Number Portability application is required for successful processing of a

particular incoming signaling message packet. While any number or variety of LNP translation applications may be simultaneously provisioned on a single LSME card, the triggerless local number portability (TLNP) application **416** is the most relevant to a general discussion of the present invention.

5 TLNP application **416** essentially contains the logic necessary to de-capsulate the original ISUP IAM message, extract the appropriate information from the de-capsulated message, and perform an associated LNP database lookup. Furthermore, the TLNP application **416** is responsible for modifying the signaling message based on the results of the

10 LNP database lookup.

In the embodiment shown in Figure 8, TLNP application process **416** is also interfaced to an Ethernet Controller process **418**, and as such is also responsible for directing incoming message packets to process **418**. Ethernet Controller process **418** serves as an internal Ethernet terminus that

15 services and administers connection, via an Ethernet communication link **460**, to the external LNP database server **450**. Correspondingly, the external LNP database server **450** includes an Ethernet Controller process **452**, which serves as an external Ethernet terminus that services and administers connection to the triggerless LNP routing node **400**, via the

20 Ethernet communication link **460**.

As shown in Figure 8, an LNP database **454** is stored within and administered by the LNP database server **450**. Such an LNP database server could be configured such that some or all of the LNP data is stored in blocks of high speed random access memory (RAM), or the LNP data could

be stored on a high density, fast access physical storage media such as magnetic or optical discs.

LSME 410 also contains an HMRT process 420 that is responsible for the routing of SS7 message packets once TLNP translation has been completed. That is, the HMRT process 420 determines to which LIM card an SS7 message packet should be routed for subsequent outbound transmission.

It will be appreciated from Figure 8 that in the case of an external LNP database server configuration, the server 450 is in communication with and serviced by the Local Service Management System (LSMS) 370, in a manner similar to that described previously. Once again, it should suffice to state that the LSMS 370 maintains the LNP database server 454 with the most current ported subscriber information available at any given time.

15 **Ethernet Connected LNP Database Server Translation Process**

Referring again to Figure 8, the path of a typical SS7 ISUP IAM signaling message requiring TLNP translation service is next traced from reception at the triggerless LNP routing node by the inbound LIM 320, through the translation process, and on to the outbound LIM 360. Once again, a detailed flow chart of TLNP related processing steps is presented in Figures 5 and 6, and may be used in conjunction with the schematic diagram shown in Figure 8 to better understand the triggerless LNP lookup methodology.

As processing steps ST1 through ST11 are essentially identical to those discussed and described above for the embodiment shown in Figure

2, a detailed discussion of these steps will not be repeated below. Instead, it will be appreciated that an incoming ISUP IAM MSU is received by LIM card 320 and, according to the process described in steps ST1 through ST11, the ISUP MSU is SCCP encapsulated and internally routed via IMT bus 310 to
5 LSME card 410 for final TLNP processing.

Beginning with step ST12, the encapsulated SCCP MSU is received and examined by SCRC process 412 that is resident on LSME 410. Given that the CdPA RI field of the SCCP MSU is set to SSN and the CdPA SSN field of the SCCP MSU is set to the LNP subsystem of the TLNP node 400,
10 SCRC process 412 forwards the encapsulated MSU to the LNPM process 414, as indicated by step ST13. In step ST14, LNPM process 414 verifies that the SCCP MSU contains an encapsulated ISUP MSU. Upon successful verification, the SCCP MSU is sent to TLNP application 416 for further processing. TLNP application processing begins with verification of the
15 pointers and field lengths associated with the ISUP message (ST15). With a positive verification at step ST15, TLNP application 416 next extracts the original ISUP MSU by removing and discarding the SCCP wrapper (ST16). The TLNP application 416 next performs a number of operations intended to validate one or more of the Called Party (CdPA) parameters contained in the
20 original ISUP MSU (ST17). Such validation operations may include, but are not limited to: verification that the Called Party Number exists; verification that the Called Party Number contains 10 digits; verification that the Nature Of Address is national; and verification that the Numbering Plan is ISDN.

With the above-described validation process successfully completed,
25 the TLNP application 416 extracts the Called Party Number from the ISUP

IAM MSU and uses this value to perform a lookup operation in LNP database 454 (ST18). In the present embodiment, it will be appreciated that the LNP database query requested by TLNP process 416 is communicated to the LNP database 454 via the high speed Ethernet type communication link 460. More particularly, TLNP process 416 communicates directly with the on-board Ethernet controller process 418 which facilitates access to the Ethernet communication link 460. The LNP database query communication is received by the external LNP database server 450, and subsequently LNP database 454, via Ethernet controller 452. It will be appreciated that a similar process, in reverse, is performed when LNP database response messages are communicated from the external LNP database server 450 to the LSME card 410. It should also be appreciated that TLNP processing node 400 of the present invention is not limited to the use of an Ethernet connection between the external LNP database server and the LSME card 410. Any number of commercially available, high-speed communication links and protocols could be easily implemented to provide the required inter-device communication functionality.

As indicated in step ST19, the Translated Call Number Indicator (TCNI) field contained within the ISUP IAM message is set to a value of one. It should be appreciated that the TCNI field is set to a value of one regardless of whether a match is found during the LNP lookup operation. In the event that an entry exists in the LNP database 454 which corresponds to the Called Party Number value in the ISUP IAM message, the Called Party Number is considered to be associated with a ported subscriber (ST20) and LNP database process 454 returns a Location Routing Number (LRN). Prior

to incorporation of the LRN value in the ISUP MSU, the original CdPA Number value used in the LNP database lookup is stored in a Generic Address Parameter (GAP) field, which is also contained within the ISUP MSU (ST21). Subsequently, the CdPA Number field of the ISUP MSU is
5 overwritten with the LRN value returned by the LNP database process 454, as indicated in step ST22.

As further indicated in step ST23, a Jurisdiction Information Parameter (JIP) may be appended to the TLNP processed ISUP MSU under certain conditions. These conditions have been described above, in detail,
10 for the previous embodiment and consequently will not be repeated below. With TLNP processing complete, the modified ISUP MSU is passed to HMRT process 420. HMRT process 420 determines to which LIM card an SS7 message packet should be routed for subsequent outbound transmission. In this case, the HMRT process 420 determines that the
15 desired outbound signaling link associated with the routing of the modified ISUP MSU is located on LIM 360. Consequently, the modified signaling message packet is internally routed across the IMT bus 310 to LIM 360, where it is generally received by the I/O queue process 362. Eventually, the modified message packet is passed from the I/O queue 362 on to the MTP
20 Level 2 and Level 1 processes 364 and 366, respectively. Once again, MTP level 1 and 2 layer processes 366 and 364, respectively, provide the facilities necessary to send and receive digital data over a particular physical media / physical interface, as well as to provide error detection / correction and sequenced delivery of all SS7 message packets transmitted into the SS7
25 network.

Sample Triggerless LNP Call Setup Message Flow

Shown in Figure 9 is a simplified network diagram that generally illustrates a sample call flow associated with a triggerless ported number call setup scenario. It will be appreciated that Figure 9 includes a telecommunications network, generally indicated by the numeral 500. Telecommunications network 500 is further comprised of a number of discrete network elements and communication terminals, many of which were presented in Figure 1. More particularly, of those components previously described in Figure 1, network 500 includes the originating End Office (EO) 110, the recipient terminating EO 112, the donor terminating EO 113, the tandem office 114, the Calling Party terminal 120, and the Called Party terminal 122. Network 500 also includes a TLNP routing node 516, which is similar in form and function to the first embodiment of the present invention described herein. As such, TLNP routing node 516 contains an internal, integrated TLNP database 518.

In this example, it is assumed that the called party 122 has had local phone service ported from a service provider that owns EO 113 to a service provider that owns EO 112. Consequently, it is implied that the service responsibility for called party 122 was transferred from the donor EO 113 to the recipient EO 112 at some point in the past. As such, EO 112 is now assumed to service called party 122. Once again, the diagram shown in Figure 9 is intended to generally illustrate the flow of SS7 call setup messages in response to the placement of a telephone call from Calling Party 120 to the ported Called Party 122. Figure 10 provides sample ISUP IAM message contents before and after the TLNP processing that is

performed in the example scenario presented in Figure 9. In Figure 10, the left hand column indicates the various fields in an IAM message. The central column illustrates exemplary field values before LNP processing, and the right hand column illustrates exemplary field values after LNP processing.

5 It will be appreciated that the fields shown in Figure 10 are a subset of the fields contained within a typical ISUP IAM message, and consequently Figure 10 is not intended to represent a complete ISUP IAM message. More particularly, Figure 10 includes sample Originating Point Code (OPC), Destination Point Code (DPC), Calling Party Number Length (CgPA:NL),
10 Calling Party Address (CgPA:ADD), Called Party Number Length (CdPA:NL), Called Party Address (CdPA:ADD), Called Party Numbering Plan (CdPA:NP), Called Party Nature of Address Indicator (CdPA:NAI), Translated Call Number Indicator (TCNI), Generic Address Parameter (GAP), and Jurisdiction Information Parameter (JIP) values.

15 As indicated in Figure 9, in response to call initiating activity performed by Calling Party 120, the originating End Office 110 formulates and launches an ISUP IAM message N1 into the SS7 signaling network. In this example, it is assumed that the EO 110 has been assigned an SS7 network address or point code (PC) of 1-1-0, while TLNP routing node 516
20 has a PC of 2-2-0, and tandem office 114 has a PC of 3-3-0. It is further assumed that the recipient EO 112 has an assigned Location Routing Number (LRN) of 9193801111, that Calling Party 120 has been assigned a phone number of 9194671234 and Called Party 122 has a phone number of 9194605500. As such, it will be appreciated from Figure 10 that ISUP IAM
25 message N1 includes calling and called party information associated with

Calling Party 120 and Called Party 122, respectively. It will also be appreciated that the OPC of the message N1 is set to 1-1-0, while the DPC is set to 3-3-0.

Returning now to the message flow shown in Figure 9, ISUP IAM message N1 is received by the TLNP routing node 516 and subsequently examined to determine whether TLNP processing is required. In this case, TLNP translation service is indicated and an LNP database lookup is performed by the TLNP sub-system 518, based on the CdPA:ADD value of 9194605500. A match is found in the LNP database, and an LRN value of 9193801111 is returned, as indicated in the sample LNP database of Figure 4. It should be appreciated that the LRN value returned by the LNP database corresponds to that of the recipient EO 112 which services the Called Party 122. Consequently, several modifications are made to the initial ISUP IAM MSU, resulting in a new ISUP IAM message N2. As indicated in Figure 10, there are a number of key differences between the N2 message and the original ISUP IAM message N1. The CdPA:ADD field of the N2 message has been changed from the previous N1 value of 9194605500 to reflect the LRN value, 9193801111, returned by the LNP database lookup operation. The Translated Call Number Indicator (TCNI) field has also been changed from the previous N1 value of 0 to the new value of 1. Two new parameters have also been added and assigned values in the N2 message. The GAP:ADD field has been set to original N1 CdPA:ADD value of 9194605500, while the JIP:ID parameter has been set to the first six digits of the N1 CgPA:ADD value, 919467.

It should be appreciated that LNP response message N2 contains a Location Routing Number (LRN) associated with the recipient EO 112. TLNP routing node 516 subsequently MTP routes message N2 to tandem office 114. Tandem office 114 examines and processes the message and
5 formulates a message N3, the contents of which are not particularly relevant to a discussion of the present invention. Message N3 is sent back to TLNP routing node 516, which in turn MTP routes the message to the recipient EO 112 as message N4.

Once again, those skilled in the art of telecommunication network
10 operations will appreciate that additional call setup and teardown messages, not shown in Figure 9, may be necessary to administer a complete a telephone call between the calling party 120 and the called party 122. The signaling message flow shown in Figure 9 is intended only to generally illustrate a TLNP translation process of the present invention. As these
15 additional signaling messages are not particularly relevant to the design and operation of the present invention, a detailed discussion of call setup and teardown procedures in an SS7 telecommunications network is not provided herein.

The triggerless number portability processing illustrated in Figure 8
20 can be contrasted with conventional triggered number portability processing illustrated in Figure 1. First, because TLNP routing node 516 determines whether number portability processing is required, originating end office 110 need not have a number portability processing trigger as required by the system in Figure 1. This is a significant advantage, since it is burdensome to
25 program multiple end offices to trigger on ported numbers.

Another advantage provided by the TLNP routing node of the present invention is a decreased number of messages for performing number portability processing. For example, eight messages are required to deliver the call setup message to called party end office 112 illustrated in Figure 1, while only four messages are required in Figure 9. This decreased message flow provided by embodiments of the present invention decreases call setup time and network congestion.

It will be understood that various details of the invention may be changed without departing from the scope of the invention. Furthermore, the foregoing description is for the purpose of illustration only, and not for the purpose of limitation—the invention being defined by the claims.

CLAIMS

What is claimed is:

1. A triggerless number portability routing node, the routing node
5 comprising:
 - (a) a communication module for receiving a first call setup
message from a first end office associated with a calling party
over a first communications network, the first call setup
message including a first called party address and a ported
10 number translation indicator;
 - (b) a stop action process for examining the ported number
translation indicator to determine whether number portability
processing is required and, in response to determining that
number portability processing is required, encapsulating the
15 first call setup message in a first packet;
 - (c) a number portability database containing packet routing
instruction records associated with ported subscribers; and
 - (d) a number portability process for receiving the first packet,
20 extracting the first called party address from the first packet,
performing a lookup in the number portability database using
the first called party address to obtain a second called party
address associated with a second end office, and modifying
the first call signaling message to include the second called
party address.

25

2. The routing node of claim 1 wherein the first call setup message is a Signaling System 7 (SS7) signaling message.

3. The routing node of claim 2 wherein the Signaling System 7 (SS7) signaling message is an ISDN User Part (ISUP) message signal unit (MSU).

4. The routing node of claim 1 wherein the first call setup message is an initial address message.

10

5. The routing node of claim 1 wherein the first communications network is a Signaling System 7 (SS7) network.

6. The routing node of claim 1 wherein the first communications network is an Internet Protocol (IP) network for carrying IP encapsulated SS7 messages.

7. The routing node of claim 1 wherein the communication module is a Signaling System 7 (SS7) Link Interface Module (LIM) adapted to receive SS7 messages over an SS7 signaling link.

8. The routing node of claim 1 wherein the communication module is an Internet Protocol (IP) Database Communication Module (DCM) adapted to receive IP-encapsulated SS7 messages over an IP network.

9. The routing node of claim 1 wherein each record in the number portability database includes a Signaling System 7 (SS7) Location Routing Number (LRN).
- 5 10. The routing node of claim 1 wherein each record in the number portability database contains an Internet Protocol (IP) destination address and port number.
- 10 11. The routing node of claim 1 wherein the stop action process is adapted to encapsulate the first call setup message in a signaling connection control part (SCCP) packet.
12. The routing node of claim 11 wherein the stop action process is adapted to set an originating point code value in the SCCP packet to a point
15 code of the routing node, an SCCP called party routing indicator value in the SCCP packet to SSN, and a called party subsystem number value in the SCCP packet to a number portability subsystem number of the routing node.
13. The routing node of claim 1 wherein the number portability
20 process is adapted to replace the first called party address with the second called party address in the first call setup message.
14. The routing node of claim 1 wherein the second called party
address is a Location Routing Number (LRN) associated with the second
25 end office.

15. The routing node of claim 1 wherein first call SETUP message includes a generic address parameter address field having a first address value and the number portability process is adapted to replace the first
5 address value with the first called party address.

16. The routing node of claim 1 wherein the first call setup message includes a Translated Call Number Indicator field having a first value and the number portability process is adapted to set the first value to
10 one.

17. The routing node of claim 1 wherein the first call setup message includes a jurisdiction indication parameter having a first value and the number portability process is adapted to set the first value to at least
15 some of the digits from a called party address value contained in the first call setup message.

18. The routing node of claim 1 wherein the number portability database is contained within the routing node.
20

19. The routing node of claim 1 wherein the number portability database is located on an external database server that is communicatively coupled to the routing node.

20. The routing node of claim 1 wherein the number portability database includes a high-speed, random access memory (RAM) for storing the packet routing instruction records.

5 21. The routing node of claim 1 wherein the number portability database includes a high speed, optical disc storage medium for storing the packet routing instruction records.

22. A method for routing a data packet associated with a ported
10 subscriber in a communications network, the method comprising the steps of:

- (a) receiving a data packet from a communication network;
- (b) determining whether the data packet contains a call setup message;
- 15 (c) in response to determining that the data packet includes a call setup message, performing a lookup in a number portability database using key information contained in the data packet;
- (d) modifying contents of the data packet to incorporate one or more number portability routing instructions returned by the
20 number portability database lookup; and
- (e) transmitting the modified data packet into the communication network.

23. The method of claim 22 wherein the data packet is a Signaling
25 System 7 (SS7) signaling message.

24. The method of claim 23 wherein the Signaling System 7 (SS7) signaling message is an ISDN User Part (ISUP) message signal unit (MSU).

5 25. The method of claim 24 wherein ISUP MSU contains an initial address message.

26. The method of claim 22 wherein the communications network is a Signaling System 7 (SS7) network.

10

27. The method of claim 22 wherein the communications network is an Internet Protocol (IP) network carrying IP encapsulated SS7 messages.

28. The method of claim 22 wherein determining whether the data
15 packet contains a call setup message includes determining whether the data packet is an SS7 ISDN User Part initial address message.

29. The method of claim 22 wherein the key information used in the number portability database lookup includes address identification
20 information associated with the called party.

30. The method of claim 29 wherein the address identification information includes the information contained in a Called Party Address (CdPA:ADD) field of the data packet.

25

31. The method of claim 22 wherein the number portability routing instruction information returned by the number portability database is a Location Routing Number.

5 32. The method of claim 22 wherein the modifying the contents of data packet includes replacing original contents of a Called Party Address (CdPA:ADD) field in the data packet with the routing instruction information returned by the number portability database lookup.

10 33. The method of claim 22 wherein the routing instruction information returned by the number portability database includes a Location Routing Number (LRN).

15 34. The method of claim 22 wherein modifying the contents of the data packet includes replacing original contents of a Generic Address Parameter Address (GAP:ADD) field in the data packet with original contents of a Called Party Address (CdPA:ADD) field in the data packet.

20 35. The method of claim 22 wherein modifying the contents of the data packet includes setting a Translated Call Number Indicator field in the data packet to a value of one.

 36. The method of claim 22 wherein modifying the contents of the data packet includes setting a Jurisdiction Information Parameter

Identification (JIP:ID) field in the data packet to a value equal to digits extracted from a Calling Party Address (CgPA:ADD) field of the data packet.

37. The method of claim 22 wherein receiving a data packet from a
5 communications network includes receiving a data packet from a first end office associated with a calling party in the communications network and transmitting the modified data packet to a tandem office in the communications network.

10 38. The method of claim 22 comprising, in response to determining that the data packet includes a call setup message and prior to performing the lookup, encapsulating the data packet in a signaling connection control part (SCCP) message.

15 39. The method of claim 38 wherein encapsulating the data packet in an SCCP packet includes setting an originating point code value in the SCCP packet to a point code of the routing node, an SCCP called party routing indicator value in the SCCP packet to SSN, and a called party subsystem number value in the SCCP packet to a number portability
20 subsystem number of the routing node.

40. The method of claim 22, wherein modifying the contents of the data packet includes setting a Jurisdiction Information Parameter field to a value for identifying an end office that originated the call setup message.

41. A computer program product comprising computer-executable instructions embodied in a computer-readable medium for performing steps comprising:

- 5 (a) receiving a call setup message from a communications network, the call setup message including a first called party address value associated with a first end office;
- (b) performing a lookup in a number portability database based on the first called party address value to obtain a second called party address value associated with a second end office; and
- 10 (c) replacing the first called party address value in the call setup message with the second called party address value.

42. The computer program product of claim 41 comprising, in response to receiving the call setup message and prior to performing the
15 database lookup, encapsulating the call setup message in a signaling connection control part (SCCP) packet.

43. The computer program product of claim 42 wherein encapsulating the call signaling message in an SCCP packet includes
20 setting a Jurisdiction Information Parameter field to a value for identifying an end office that originated that call setup message.

44. The computer program product of claim 41 wherein the call setup message includes a first calling party address value and a first
25 jurisdiction information parameter value.

45. The computer program product of claim 44 comprising modifying the first jurisdiction information parameter value to include at least a portion of the first calling party address value.

5

46. The computer program product of claim 41 wherein receiving a call setup message includes receiving an ISDN user part (ISUP) message.

47. The computer program product of claim 41 comprising, after
10 replacing the first called party address value with the second called party address value, forwarding the first call setup message to a tandem switch.




Figure 1
(PRIOR ART)




Figure 2




Figure 3

(PRIOR ART)

348

LNP DATABASE	
KEY	DATA FIELDS
<u>CdPA:ADD</u> 9194605500 2123675637 7704545731 2125662322	<u>LRN</u> 9193801111 2023211234 3033211234 1013211234

Figure 4




Figure 5




Figure 6




Figure 7




Figure 8

500 →




Figure 9

FIELD	N1	N2
OPC	1-1-0	1-1-0
DPC	3-3-0	3-3-0
CgPA:NL	7	7
CgPA:ADD	9194671234	9194671234
CdPA: NL	7	7
CdPA:ADD	9194605500	9193801111
CdPA:NP	1	1
CdPA:NAI	NATIONAL	NATIONAL
TCNI	0	1
GAP:ADD	--	9194605500
JIP:ID	--	919467

Figure 10

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US00/03880

A. CLASSIFICATION OF SUBJECT MATTER IPC(7) : H04M 7/00; H04J 3/12 US CL : 370/522, 524; 379/229, 230, 231; 455/435 According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) U.S. : 370/522, 524; 379/229, 230, 231; 455/435 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) number\$3 adj1 portabilit\$4		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X,P	US 5,949,871 A (KABAY et al) 07 September 1999, col.1, line 8 to col.6, line 14.	1-47
Y	US 5,625,681 A (BUTLER, II) 29 April 1997, col.1, line 10 to col.3, line 4.	1-47
Y	US 5,602,909 A (CARKNER et al) 11 February 1997, col.1, line 11 to col.4, line 4.	1-47
Y	US 5,598,464 A (HESS et al) 28 January 1997, col.1, line 14 to col.2, line 14.	1-47
Y	US 5,586,177 A (FARRIS et al) 17 December 1996, col.4, line 5 to col.5, line 16.	1-47
Y	US 5,572,579 A (ORRISS et al) 05 November 1996, col.1, line 30 to col.4, line 43.	1-47
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* "A"	Special categories of cited documents. document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E"	earlier document published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O"	document referring to an oral disclosure, use, exhibition or other means	
"P"	document published prior to the international filing date but later than the priority date claimed	"F" document member of the same patent family
Date of the actual completion of the international search 19 MAY 2000		Date of mailing of the international search report 21 JUN 2000
Name and mailing address of the ISA, US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230		Authorized officer PHUONGCHAU BA NGUYEN Telephone No. (703) 305-9509

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US00/03880

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5,550,914 A (CLARKE et al) 27 August 1996, col.1, line 19 to col.4, line 59.	1-47
Y	US 5,546,398 A (TUCKER et al) 13 August 1996, col.1, line 7 to col.3, line 15.	41-47